City of Burnaby

BOARD OF VARIANCE REFERRAL LETTER

DATE: Feb 4, 2016	**DEADLINE: Feb 9, 2016 for the March 3, 2016 hearing**	*This is **not** an application. Please take letter to Board of Variance. (Clerk's office - Ground Floor)*
NAME OF APPLICANT: Terrence Clark		
ADDRESS OF APPLICANT: 4277 Prospect Road, North Van. V7N 3L6		
TELEPHONE: 604.318.3315		

PROJECT			
DESCRIPTION: New single family dwelling			
ADDRESS: 4412 Albert St			
LEGAL:	**LOT: 3**	**DL: 121**	**PLAN: 1054**

The above mentioned application, which includes the attached plan of the proposal, has been refused by the Building Department on the basis of contravention of:

Zone/Section(s) RM6 [206.2(2) to R5-105.9]
of the Burnaby Zoning Bylaw No. 4742

COMMENTS:

The applicant is proposing to build a new single family dwelling. The following relaxation is being requested.

1) The front yard setback, to the porch post, will be 22.72 feet where a minimum front yard setback of 24.88 feet is required based on front yard averaging. The porch post projects 1.5 feet beyond the foundation.

Note: The applicant recognizes that should the project contain additional characteristics in contravention of the zoning by-law a future appeal(s) may be required.

BHS

Peter Kushnir
Deputy Chief Building Inspector

TOPOGRAPHIC PLAN OF LOT 3, BLOCK 5
DISTRICT LOT 121, GROUP 1
NEW WESTMINSTER DISTRICT
PLAN 1054

ZONING: RM6

NOTE:
Elevations are based on geodetic datum
Bench Mark - control Monument
MTS 96 located in the curb at the NE corner of Rosser Street and Albert Street
MV Elevation = 28.42 feet
(TBM elevation)

4412 ALBERT STREET

SCHEDULE OF ADJACENT DWELLINGS			
ADDRESS NO	LOT NO	MIN PROJECT SETBACK	AVERAGE
4404	1	9.14	9.21
4410	2	9.27	
4416	4	9.17	MINIMUM
4427	LMS2334	7.16	6.40
	TOTAL	35.74	

NOTE:
The building envelope shown is only our interpretation of the City of Burnaby building bylaws. The size and location of the building envelope must be confirmed by the City of Burnaby planning department prior to any design work. Failure to confirm with the planning department will place the responsibility onto the house designer.

concrete sidewalk

BOY REFERRAL

FUJI TO POST

22.72'

FUJI APPLES

RM6 → RS

dwelling with basement

3

1

2

Lot Area:
4037.4 sqft

4

4416
2 storey dwelling with basement

LMS2334

A

veranda

Balcony above
Lid below

4427
2 storey multiplex with basement

ROSSER AVENUE

LANE

(fully paved)

edge of pavement

center line

SITE PLAN
1/8" = 1'-0"

LEGEND:

OIP	old iron post found
OLP	old lead plug found
IP	iron post placed
LP	lead plug placed
OAP	old aluminum post found
TW	top of wall
TSW	top of sidewalk
GT	gutter
CP	covered porch
LQ	living quarters
o/h	overhang
(G)	ground

NOTE
For construction use lead plugs in sidewalk or only survey monument only, for elevation control

NOTES:
Measurements & contour lines surveyed & field checked by owner
(verify to depart)

©COPYRIGHT EXACT DRAFTING INC. ALL RIGHTS RESERVED. THIS PLAN AS AND AT ALL TIMES REMAINS THE EXCLUSIVE PROPERTY OF EXACT DRAFTING INC. AND CANNOT BE USED OR REPRODUCED WITHOUT EXACT DRAFTING INC'S WRITTEN CONSENT.

THIS DRAWING WAS PREPARED BY EXACT DRAFTING INC. THE MATERIAL IN IT REFLECTS THE BEST JUDGEMENT OF EXACT DRAFTING INC. IN LIGHT OF THE INFORMATION AVAILABLE TO IT AT THE TIME OF PREPARATION. ANY USE WHICH A THIRD PARTY MAKES OF THIS DRAWING, OR ANY RELIANCE ON OR DECISIONS TO BE MADE BASED ON IT, ARE THE RESPONSIBILITY OF SUCH THIRD PARTIES. EXACT DRAFTING INC. ACCEPTS NO RESPONSIBILITY FOR DAMAGES, IF ANY, SUFFERED BY ANY THIRD PARTY AS A RESULT OF DECISIONS MADE OR ACTIONS TAKEN BASED ON THIS DRAWING.

DRAWN BY: Exact Drafting Inc.
Phone: 604-526-3395
Fax: 604-526-3391
Email: exact@shaw.ca

Terrence Clark
4411 Prospect Road
North Vancouver
604-988-3395

4412 ALBERT STREET
PROPOSED HOUSE
SITE PLAN

A1 | 01 | 1/4"=1'-0"

GENERAL NOTES:

- DIMENSIONS LISTED FOR THE REVISED ST. ROAD ARCHITECT AND ALL CONTRACTORS TO BE THE STANDARDS OF THE NATIONAL BUILDING CODE OF CANADA 2005 AND THE BUILDING CODE ACT.
- CONTRACTOR SHALL VERIFY ALL DIMENSIONS AND CONDITIONS ON THE SITE.
- THE MINIMUM SIZE OF STRUCTURAL MEMBERS AS DEFINED CONSTRUCTION CODE AND PLANS REQUIREMENTS ETC. MAY CHANGE IN SOME LOCATIONS WITH BOTH THE ARCHITECTURAL DESIGN DEPARTMENT WHICH HAVE PLAN REVIEW OTHER ASSOCIATIONS IF PLACING PAPER THEIR REQUIREMENTS.
- CONSTRUCTION SHALL CONFORM WITH THE LOCAL BUILDING CODES & REGULATIONS.
- WORK TO BE DONE UNLESS OTHERWISE NOTED.
- WHERE A CONTRACTOR TO REVIEW WORK OR REPORT POSSIBLE PROBLEMS WHEN IS AN ISSUES.
- IT IS THE RESPONSIBILITY OF OWNER & CONTRACTOR TO VERIFY ALL ASPECTS OF ALL PROJECT.
- THE OWNERS AND ALL SUB TRADES RESPONSIBILITY FOR ALL INFORMATION PRESENTED WITH THIS PROJECT.
- DRAWING MUST NOT BE REPRODUCED TO THE WORK BEFORE PERMIT ISSUES & OTHER PLAN REVIEW REVISIONS AT TIME OF CONSTRUCTION.
- CONTRACTOR MUST ALL SUBTRADES CHECK ALL DIMENSIONS IN ACCURANCE TO SECTIONS AND THE SECTION CODE ARE WORKING ACCORDING TO THE OF BUILDING CODE.
- MATERIALS FOR DRAINAGE ON BASEMENT & FOUNDATION.

GENERAL REQUIREMENTS:

- ALL LOAD BEARING ROOF MEMBERS SHALL BE AS GRADE DESIGN FOR DRY BETTER AND FOOL CONFORM TO TABLE 4.4 FORMED PART OF METALLIC SYSTEM DESIGN.
- CONCRETE MIX SHALL BE 1 PART CEMENT 1 PART SAND AND 3 PARTS COARSE AGGREGATE UP TO 19 MM IN SIZE OR 1 PART CEMENT AND 4½ PARTS DRY PLAN GRAVEL.
- CONCRETE FOR REINFORCED FOOTING & FOUNDATION WALL SHALL HAVE A MINIMUM COMPRESSIVE STRENGTH OF 40000 PSI WITH 28 DAYS.
- ALL TIMBER LUMBER SHALL BE MINIMUM #2 NO. GRADE UNLESS OTHERWISE NOTED. STEEL LUMBER SHALL BE AS PER NATIONAL BUILDING CODE OF CANADA & ALL BUILDING CODE ACT.
- ALL LATTICE FOR EXTERIOR AND LOAD BEARING WALL OPENINGS SHALL BE MINIMUM 3-1 1/2" UNLESS OTHERWISE NOTED.
- PLUMBING SHALL CONFORM TO BUILDING SECTION 4.9.
- HEATING INSTALLATION SHALL CONFORM TO BUILDING SECTION 4.10 AND SECTION 4.11.
- ELECTRICAL WORK CONFORM TO BUILDING SECTION 4.12.

FRAMING NOTES

- FLOOR DESIGN COMPONENT SIZE & SPACING SHALL REVIEW & REVISION BY STRUCTURAL ENGINEER IF REQUIRED.
- PLANKS AS REQUIRED.
- WOOD JOISTS MAX 2'-0" OC AS NOTED.
- METAL HANGERS & BRACKETS AS REQUIRED.
- FLOOR LOADS LIVE LOADS DESIGNED & STRUCTURE @ 1'-0" OC.
- UNLIMITED BEAMS & LINTELS ARE 1-1 1/2" DIA BEAMS.
- EXCEPTIONS TO TYP. SPECS NOTED BEFORE THEY OCCUR.
- DRAWINGS & DIMENSIONS TO BE VERIFIED BY OWNER.
- FLOOR LOADS TO SUIT DESIGN.

SECTION NOTES

1. ROOF CONSTRUCTION
ASPHALT SHINGLES OR TO SUIT OWNER
½" PLYWOOD
ASPHALT IMPREGNATED SHEATHING PAPER
2"x4" UP SLOPE
ENGINEERED TRUSSES @ 24" O.C. PER CERTIFICATE AND FRAMING PLANS
R 40 BATT INSULATION (VENT AS PER CODE)
6 MIL PVB
½" DRYWALL CEILING

1A. ROOF CONSTRUCTION
ASPHALT SHINGLES OR TO SUIT OWNER
½" PLYWOOD
ASPHALT IMPREGNATED SHEATHING PAPER
2"x4" UP SLOPE
2"x10" ROOF JOISTS @ 16" O.C. (2"x4" PURLINS)
R 40 BATT INSULATION (VENT AS PER CODE)
6 MIL PVB
½" DRYWALL CEILING

2. EAVES CONSTRUCTION
CONTINUOUS GUTTER OR TO SUIT
1-2"x8" FASCIA BOARD
PRE FINISHED ALUMINUM VENTED SOFFIT

3. FLOOR CONSTRUCTION
FINISH FLOORING TO SUIT OWNER
¾" T & G PLYWOOD GLUED AND SCREWED
2"x10" FLOOR JOISTS @ 16" O.C. OR AS SPECIFIED
2"x4" LOAD BEARING AND STRAPPING @1'-0" O.C. OR ACCEPTABLE ALTERNATIVE
½" DRYWALL CEILING

4. CRAWL SPACE, BASEMENT & SLAB ON GRADE FLOOR CONSTRUCTION
6" SLAB (CAR) – CRAWL SPACE
4½" CONCRETE SLAB – BASEMENT
6 MIL PVB
6" GRANULAR FILL
VENTILATION (ACC)

5. EXTERIOR WALL CONSTRUCTION
FINISH TO SUIT OWNER
½"x8" PLYWOOD (ACC)
APPROPRIATE SHEATHING MEMBRANE
½" PLYWOOD SHEATHING
2"x6" STUDS (ACC) @ 16" (GARAGE)
STUDS (ACC) @ 24" O.C.
R 20 BATT INSULATION (GARAGE UNINSULATED)
6 MIL PVB
½" DRYWALL

6. INTERIOR WALL CONSTRUCTION
½" DRYWALL BOTH SIDES
2"x4" STUDS (ACC) @ 16" O.C.

7. FOUNDATION WALL CONSTRUCTION
2"x6" SILL PLATE (CAN REAL CHARGE)
ANCHOR BOLTS @ 6'-0" O.C.
8" CONCRETE FOUNDATION WALL !
DRAIN PROVIDED TO EXTERIOR PERIMETER (2 LAYERS MIN 6-12" FROM INSULATION TO ASPHALT
24"x8" CONCRETE FOOTING CONTINUOUS

8. PONY WALL CONSTRUCTION
2"x6" STUDS @16" O.C.
2"x6" SILL PLATE (CAN REAL CHARGE)
ANCHOR BOLTS @6'-0" O.C.
ONLY CONCRETE FOUNDATION WALL HEIGHT TO BE DETERMINED BY SITE CONTRACTOR & CODE ENGINEERING MAY BE REQUIRED

9. REAR DECK/LANDING CONSTRUCTION
REUSABLE LOW WATERPROOF MEMBRANE
2"x6" DECK JOISTS @16" O.C. OR AS NOTED
CONSULT DECKING MANUFACTURER OR OWNER

10. DRAINAGE
DRAIN PROVIDED AROUND FOOTING PERIMETER
6" GRANULAR FILL

11. MECHANICAL
CONSULT MECHANICAL ENGINEER FOR INSTALLATION & CODE REQUIREMENTS

12. SPRINKLER
ENGINE DESIGNED TO CODE REQUIREMENTS CONSULT AUTHORIZED SPRINKLER SUPPLIER OR INSTALLER

13. RADIANT HEATING
6" POURED CONCRETE TOPPING ON RADIANT FLOORING HEATING SYSTEM ALLOW FOR EXTRA BALL PLATE VERIFY BUILDING HEIGHT & CONSULT STRUCTURAL ENGINEER FOR LOAD REQ'S

CALCULATIONS

ZONE:	R4A – RR	LOT AREA	4,000 SQFT	PROPOSED	ALLOWED
FLOOR AREA:		SITE COVERAGE (%SR)		1984 SQFT	2400 SQFT
BASEMENT EXCLUDED	1,174 SQFT	FLOOR SPACE RATIO (FSR)		3422 SQFT	3422.84 SQFT
MAIN FLOOR PROPOSED	1,174 SQFT	HEIGHT (STORY)		2.5+A STORY	2.5+A STORY
UPPER FLOOR PROPOSED	1,074 SQFT	DEPTH (FEET)		37'-4" FEET	37'-4" FEET
GARAGE (INCLUDED)	462 SQ FT	FRONT DEPTH		102 SQFT	462 SQFT

DOOR AND FRAME SCHEDULE

MARK	Style	DOOR SIZE WD	DOOR SIZE HGT	DOOR SIZE THK	DOOR MATL	DOOR GLAZING	LOWER WD	LOWER HGT	FRAME MATL	FRAME EL	FRAME DETAIL HEAD	FRAME DETAIL JAMB	FRAME DETAIL SILL	FIRE RATING LABEL	HARDWARE SET NO	HARDWARE KEYSWEE RM NO	NOTES
101	Hinged – Single	2'-8"	7'-0"	1 3/4"	—	—	0"	0"	—	—	—	—	—	—	—	—	—
102	Hinged – Single	2'-8"	7'-0"	1 3/4"	—	—	0"	0"	—	—	—	—	—	—	—	—	—

DOOR AND FRAME SCHEDULE

MARK	Style	DOOR SIZE WD	DOOR SIZE HGT	DOOR SIZE THK	DOOR MATL	DOOR GLAZING	LOWER WD	LOWER HGT	FRAME MATL	FRAME EL	FRAME DETAIL HEAD	FRAME DETAIL JAMB	FRAME DETAIL SILL	FIRE RATING LABEL	HARDWARE SET NO	HARDWARE KEYSWEE RM NO	NOTES
201	Hinged – Double – Full Lite	6'-0"	7'-8"	1 3/4"	—	—	0"	0"	—	—	—	—	—	—	—	—	—
202	Hinged – Single – Full Lite	3'-0"	6'-8"	1 3/4"	—	—	0"	0"	—	—	—	—	—	—	—	—	—
203	Bifold – Double	6'-0"	6'-8"	1 3/4"	—	—	0"	0"	—	—	—	—	—	—	—	—	—
204	Hinged – Single	2'-0"	6'-8"	1 3/4"	—	—	0"	0"	—	—	—	—	—	—	—	—	—
205	Hinged – Single	2'-0"	6'-8"	1 3/4"	—	—	0"	0"	—	—	—	—	—	—	—	—	—
206	Bifold – Double	6'-0"	6'-8"	1 3/4"	—	—	0"	0"	—	—	—	—	—	—	—	—	—
207	Pocket – Single	2'-6"	6'-8"	1 3/8"	—	—	0"	0"	—	—	—	—	—	—	—	—	—
208	Hinged – Single	2'-6"	6'-8"	1 3/4"	—	—	0"	0"	—	—	—	—	—	—	—	—	—
209	Hinged – Single	2'-6"	6'-8"	1 3/4"	—	—	0"	0"	—	—	—	—	—	—	—	—	—
210	Bifold – Double	5'-0"	6'-8"	1 3/4"	—	—	0"	0"	—	—	—	—	—	—	—	—	—
211	Bifold – Double	5'-0"	6'-8"	1 3/4"	—	—	0"	0"	—	—	—	—	—	—	—	—	—
212	Hinged – Single	2'-6"	6'-8"	1 3/4"	—	—	0"	0"	—	—	—	—	—	—	—	—	—

WINDOW SCHEDULE

MARK	Style	SIZE Width	SIZE HEIGHT	TYPE	MATERIAL	NOTES
101	Picture	1'-0"	4'-0"	—	—	—
102	Picture	1'-0"	4'-0"	—	—	—
103	Glider	3'-0"	3'-0"	—	—	—
104	Picture	1'-0"	4'-0"	—	—	—
105	Awning	2'-0"	1'-0"	—	—	—
106	Glider	3'-0"	3'-0"	—	—	—
107	Picture Top 3-0th + Awning 2-0th Bottom	6'-0"	4'-0"	—	—	—
108	single Hung	2'-0"	5'-0"	—	—	—
109	single Hung	2'-0"	5'-0"	—	—	—
110	Picture	8'-0"	1'-6"	—	—	—

DOOR AND FRAME SCHEDULE

MARK	Style	DOOR SIZE WD	DOOR SIZE HGT	DOOR SIZE THK	DOOR MATL	DOOR GLAZING	LOWER WD	LOWER HGT	FRAME MATL	FRAME EL	FRAME DETAIL HEAD	FRAME DETAIL JAMB	FRAME DETAIL SILL	FIRE RATING LABEL	HARDWARE SET NO	HARDWARE KEYSWEE RM NO	NOTES
301	Hinged – Double – Full Lite	6'-0"	7'-8"	1 3/4"	—	—	0"	0"	—	—	—	—	—	—	—	—	—
302	Hinged – Single	2'-6"	6'-8"	1 3/4"	—	—	0"	0"	—	—	—	—	—	—	—	—	—
303	Bifold – Double	5'-0"	6'-8"	1 3/4"	—	—	0"	0"	—	—	—	—	—	—	—	—	—
304	Bifold – Double	5'-0"	6'-8"	1 3/4"	—	—	0"	0"	—	—	—	—	—	—	—	—	—
305	Hinged – Single	2'-6"	6'-8"	1 3/4"	—	—	0"	0"	—	—	—	—	—	—	—	—	—
306	Hinged – Single	2'-6"	6'-8"	1 3/4"	—	—	0"	0"	—	—	—	—	—	—	—	—	—
307	Bifold – Single	2'-0"	6'-0"	1 3/4"	—	—	0"	0"	—	—	—	—	—	—	—	—	—
308	Bifold – Double	4'-0"	6'-0"	1 3/4"	—	—	0"	0"	—	—	—	—	—	—	—	—	—
309	Pocket – Single	2'-6"	6'-8"	1 3/8"	—	—	0"	0"	—	—	—	—	—	—	—	—	—
310	Hinged – Single	2'-6"	6'-8"	1 3/4"	—	—	0"	0"	—	—	—	—	—	—	—	—	—
311	Bifold – Double	5'-0"	6'-8"	1 3/4"	—	—	0"	0"	—	—	—	—	—	—	—	—	—

WINDOW SCHEDULE

MARK	Style	SIZE Width	SIZE HEIGHT	TYPE	MATERIAL	NOTES
201	Glider	1'-0"	2'-0"	—	—	—
202	Picture	1'-0"	4'-0"	—	—	—
203	Picture	1'-0"	5'-0"	—	—	—
204	Picture	1'-0"	4'-0"	—	—	—
205	Picture	1'-0"	4'-0"	—	—	—
206	Awning	2'-0"	1'-0"	—	—	—
207	single Hung	1'-0"	5'-0"	—	—	—
208	Glider	5'-0"	5'-0"	—	—	—
209	Picture Top 3-0th + Awning 2-0th Bottom	6'-0"	4'-0"	—	—	—
210	single Hung	2'-0"	5'-0"	—	—	—
211	single Hung	2'-0"	5'-0"	—	—	—
212	Picture	8'-0"	1'-6"	—	—	—



1 SECTION
1/4" = 1'-0"

©2021 EXACT DRAFTING INC. ALL RIGHTS RESERVED. THIS PLAN IS AND AT ALL TIMES REMAINS THE EXCLUSIVE PROPERTY OF EXACT DRAFTING INC. AND CANNOT BE USED OR REPRODUCED WITHOUT EXACT DRAFTING INC'S WRITTEN CONSENT.

THIS DRAWING WAS PREPARED BY EXACT DRAFTING INC. THE MATERIAL IN IT REFLECTS THE BEST JUDGEMENT OF EXACT DRAFTING INC. IN LIGHT OF THE INFORMATION AVAILABLE TO IT AT THE TIME OF PREPARATION AND USE WHICH A THIRD PARTY MAKES OF THIS DRAWING OR ANY RELIANCE ON OR DECISIONS TO BE MADE BASED ON IT ARE THE RESPONSIBILITY OF SUCH THIRD PARTIES. EXACT DRAFTING INC. ACCEPTS NO RESPONSIBILITY FOR DAMAGES, IF ANY, SUFFERED BY ANY THIRD PARTY AS A RESULT OF DECISIONS MADE OR ACTIONS BASED ON THIS DRAWING.

DRAWN BY Exact Drafting Inc.
DESIGN BY Terrence Glark
4411 Prospect Road
NORTH VANCOUVER
604-985-7595

PROJECT 4412 ALBERT STREET
PROPOSED HOME
SECTION AND NOTES

SCALE 1/4"=1'-0"

SHEET A2
REV 01



1 NORTH ELEVATION
1/4" = 1'-0"



4 WEST ELEVATION
1/4" = 1'-0"

2 SOUTH ELEVATION
1/4" = 1'-0"



3 EAST ELEVATION
1/4" = 1'-0"

	EXISTING GRADE	LIMITING GRADE	ESTIMATED TERMINATED	EXISTING WINDOW AREA	TERMINATED WINDOW AREA
A	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]
B	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]

NOTE: THE CONTRACTOR SHALL CHECK AND VERIFY THE PLANS IN ALL ASPECTS BEFORE THE CONTRACT PROPERLY OF ANY DISCREPANCY BE REPORTED TO THE ARCHITECT. ANY WORK DONE BEFORE EXACT DRAFTING IS NOTIFIED IS AT THE OWNER'S RISK.

THIS DRAWING HAS BEEN PREPARED IN ACCORDANCE WITH THE WRITTEN INSTRUCTIONS OF THE OWNER. EXACT DRAFTING INC. DISCLAIMS ALL RESPONSIBILITY FOR ANY USE OF THIS DRAWING FOR ANY PURPOSE OTHER THAN THE PURPOSE INDICATED. THE DRAWING MAY NOT BE REPRODUCED OR REVISED WITHOUT EXACT DRAFTING INC.'S WRITTEN CONSENT.

Exact Drafting Inc.

Terrence Clark
4411 Prospect Road
North Vancouver
604-985-7595

4412 ALBERT STREET
PROPOSED HOME
ELEVATIONS

A4

1/4" = 1'-0"

01



FLOOR PLAN
1/4" = 1'-0"



3 SOUTH ELEVATION
1/4" = 1'-0"



5 EAST ELEVATION
1/4" = 1'-0"



4 NORTH ELEVATION
1/4" = 1'-0"



6 WEST ELEVATION
1/4" = 1'-0"



2 SECTION
1/4" = 1'-0"

DOOR AND FRAME SCHEDULE

MARK	Style	DOOR SIZE WD	DOOR SIZE HGT	DOOR SIZE THK	DOOR MATL	GLAZING	LOUVER WD	LOUVER HGT	FRAME MATL	FRAME EL	DETAIL HEAD	DETAIL JAMB	DETAIL SILL	FIRE RATING LABEL	HARDWARE SET NO	HARDWARE KEYSIDE RM NO	NOTES
1	Overhead - Sectional	16'-0"	6'-8"	1 3/4"	—	—	0"	0"	—	—	—	—	—	—	—	—	—
2	Overhead - Sectional	8'-0"	6'-8"	1 3/4"	—	—	0"	0"	—	—	—	—	—	—	—	—	—
3	Hinged - Single	3'-0"	6'-8"	1 3/4"	—	—	0"	0"	—	—	—	—	—	—	—	—	—
4	Hinged - Single	3'-0"	6'-8"	1 3/4"	—	—	0"	0"	—	—	—	—	—	—	—	—	—

WINDOW SCHEDULE

MARK	Style	SIZE Width	SIZE Height	TYPE	MATERIAL	NOTES
1	Glider	4'-0"	3'-0"	—	—	—
2	Glider	4'-0"	3'-0"	—	—	—

©2017 EXACT DRAFTING INC. ALL RIGHTS RESERVED. THIS PLAN IS USE AT ALL TIMES REMAINS THE EXCLUSIVE PROPERTY OF EXACT DRAFTING INC. AND CANNOT BE USED OR REPRODUCED WITHOUT EXACT DRAFTING INC'S WRITTEN CONSENT.

THIS DRAWING WAS PREPARED BY EXACT DRAFTING INC. THE INFORMATION IN IT REFLECTS THE BEST JUDGEMENT OF EXACT DRAFTING INC. IN LIGHT OF THE INFORMATION AVAILABLE TO IT AT THE TIME OF PREPARATION. ANY USE WHICH A THIRD PARTY MAKES OF THIS DRAWING, OR ANY RELIANCE ON OR DECISIONS TO BE MADE BASED ON IT, ARE THE RESPONSIBILITY OF SUCH THIRD PARTIES. EXACT DRAFTING INC. ACCEPTS NO RESPONSIBILITY FOR DAMAGES, IF ANY, SUFFERED BY ANY THIRD PARTY AS A RESULT OF DECISIONS MADE OR ACTIONS TAKEN BY THIS DRAWING.

DRAWN BY: Exact Drafting Inc.
EXACT DRAFTING 25 Years in the biz
Tel: (604) 940-3131

CLIENT: Terrence Gluck
4417 Prospect Road
North Vancouver
604-988-3386

ADDRESS: 446 ALBERT STREET
PROPOSED NEW GARAGE

SHEET: A5
SCALE: 1/4"=1'-0"
REV: 01

2x6 JOIST WALL
(6 Mm FIBRE-CEMENT BOARD SIDING)

MINIMUM REQUIRED EFFECTIVE THERMAL RESISTANCE = RSI 1.78 (R 10.1)
2x6 STUDS @ 16" O.C. W/ R22 BATT INSULATION IN CAVITY

MATERIAL ELEMENTS	
• INTERIOR AIR FILM	.120
• ½" GYPSUM BOARD	.079(2)
• ½" PLYWOOD SHEATHING	.127(1)
• AIR BARRIER/SHEATHING MEMBRANE	0
• ¾" CAPILLARY BREAK GAP/AIR	.156
• 6 Mm (¼") FIBRE-CEMENT SIDING	.020
• EXTERIOR AIR FILM	.030
	RSI(2.7)(R15.4)
CAVITY RSI (R-VALUE)	RSI = 3.7(R21)
TOTAL EFFECTIVE INSULATION VALUE	RSI = 4.1(R23)

2x6 JOIST SPACE
(HOLLOW BACKED VINYL SIDING)

MINIMUM REQUIRED EFFECTIVE THERMAL RESISTANCE = RSI 1.78 (R 10.1)
2x6 STUDS @ 16" O.C. W/ R22 BATT INSULATION IN CAVITY

MATERIAL ELEMENTS	
• INTERIOR AIR FILM	.120
• ½" GYPSUM BOARD	.079(2)
• ½" PLYWOOD SHEATHING	.127(1)
• SHEATHING MEMBRANE	0
• HOLLOW BACKED VINYL SIDING	.120
• EXTERIOR AIR FILM	.030
	RSI(2.6)(R14.8)
CAVITY RSI (R-VALUE)	RSI = 3.7(R21)
TOTAL EFFECTIVE INSULATION VALUE	RSI = 3.9(R22)

2x6 JOIST SPACE W/ 6 REMOVED BLOCKS
(6 Mm FIBRE-CEMENT BOARD SIDING)

MINIMUM REQUIRED EFFECTIVE THERMAL RESISTANCE = RSI 1.78 (R 10.1)
2x6 STUDS @ 16" O.C. W/ R22 BATT INSULATION IN CAVITY

MATERIAL ELEMENTS	
• INTERIOR AIR FILM	.120
• 2-½" GYPSUM BOARD	.079(2)
• ½" PLYWOOD SHEATHING	.127(1)
• SHEATHING MEMBRANE	0
• HOLLOW BACKED VINYL SIDING	.120
• EXTERIOR AIR FILM	.030
	RSI(2.6)(R14.8)
CAVITY RSI (R-VALUE)	RSI = 3.8(R22)
TOTAL EFFECTIVE INSULATION VALUE	RSI = 4.1(R23)

2x6 JOIST SPACE W/ 6 REMOVED BLOCKS
(HOLLOW BACKED VINYL SIDING)

MINIMUM REQUIRED EFFECTIVE THERMAL RESISTANCE = RSI 1.78 (R 10.1)
2x6 STUDS @ 16" O.C. W/ R22 BATT INSULATION IN CAVITY

MATERIAL ELEMENTS	
• INTERIOR AIR FILM	.120
• 2-½" GYPSUM BOARD	.079(2)
• ½" PLYWOOD SHEATHING	.127(1)
• SHEATHING MEMBRANE	0
• HOLLOW BACKED VINYL SIDING	.120
• EXTERIOR AIR FILM	.030
	RSI(2.6)(R14.8)
CAVITY RSI (R-VALUE)	RSI = 3.8(R22)
TOTAL EFFECTIVE INSULATION VALUE	RSI = 4.1(R23)

ABOVE GRADE WALL ASSEMBLY
(6 Mm FIBRE-CEMENT BOARD SIDING)

MINIMUM REQUIRED EFFECTIVE THERMAL RESISTANCE = RSI 1.78 (R 10.1)
2x6 STUDS @ 16" O.C. W/ R22 BATT INSULATION IN CAVITY

ASSEMBLY DESCRIPTION	
• INTERIOR AIR FILM	
• ½" GYPSUM BOARD	
• 6 MIL POLY VAPOUR BARRIER	
• 2x6 STUDS @ 16" O.C.	
• R 19 (R20) COMPRESSED BATT FIBREGLASS INSULATION IN CAVITIES	
• ½" PLYWOOD SHEATHING	
• AIR BARRIER/SHEATHING MEMBRANE	
• ¾" CAPILLARY BREAK GAP/AIR	
• 6 Mm (¼") FIBRE-CEMENT CLADDING	
• EXTERIOR AIR FILM	
MATERIAL ELEMENTS	
• INTERIOR AIR FILM	.120
• ½" GYPSUM BOARD	.079(2)
• 6 MIL POLY VAPOUR BARRIER	0
• ½" PLYWOOD SHEATHING	.127(1)
• AIR BARRIER/SHEATHING MEMBRANE	0
• ¾" CAPILLARY BREAK GAP/AIR	.156
• 6 Mm (¼") FIBRE-CEMENT CLADDING	.020
• EXTERIOR AIR FILM	.030
	RSI(2.7)(R15.4)
CAVITY RSI (R-VALUE)	RSI = 3.7(R21)
TOTAL EFFECTIVE INSULATION VALUE	RSI = 4.1(R23)

ABOVE GRADE WALL ASSEMBLY
(HOLLOW BACKED VINYL SIDING)

MINIMUM REQUIRED EFFECTIVE THERMAL RESISTANCE = RSI 1.78 (R 10.1)
2x6 STUDS @ 16" O.C. W/ R22 BATT INSULATION IN CAVITY

ASSEMBLY DESCRIPTION	
• INTERIOR AIR FILM	
• ½" GYPSUM BOARD	
• 6 MIL POLY VAPOUR BARRIER	
• 2x6 STUDS @ 16" O.C.	
• R 19 (R20) COMPRESSED BATT FIBREGLASS INSULATION IN CAVITIES	
• ½" PLYWOOD SHEATHING	
• AIR BARRIER/SHEATHING MEMBRANE	
• ¾" CAPILLARY BREAK GAP/AIR	
• HOLLOW BACKED VINYL SIDING	
• EXTERIOR AIR FILM	
MATERIAL ELEMENTS	
• INTERIOR AIR FILM	.120
• ½" GYPSUM BOARD	.079(2)
• 6 MIL POLY VAPOUR BARRIER	0
• ½" PLYWOOD SHEATHING	.127(1)
• AIR BARRIER/SHEATHING MEMBRANE	0
• ¾" CAPILLARY BREAK GAP/AIR	.156
• HOLLOW BACKED VINYL SIDING	.120
• EXTERIOR AIR FILM	.030
	RSI(2.7)(R15.4)
CAVITY RSI (R-VALUE)	RSI = 3.7(R21)
TOTAL EFFECTIVE INSULATION VALUE	RSI = 4.1(R23)



ABOVE GRADE WALL ASSEMBLY
1/4" = 1'-0"

BELOW GRADE WALL ASSEMBLY

MINIMUM REQUIRED EFFECTIVE THERMAL RESISTANCE = RSI 1.78 (R 10.1)
2x6 STUDS @ 16" O.C.

MATERIAL DESCRIPTION	
• INTERIOR AIR FILM	
• ½" GYPSUM BOARD	
• 6 MIL POLY VAPOUR BARRIER	
• 2x6 STUDS @ 16" O.C.	
• 4" XPS INSULATION	
• ½" PLYWOOD SHEATHING	
• AIR BARRIER/SHEATHING MEMBRANE	
• ¾" CAPILLARY BREAK GAP/AIR	
• 6 Mm (¼") FIBRE-CEMENT CLADDING	
• EXTERIOR AIR FILM	
MATERIAL ELEMENTS	
• INTERIOR AIR FILM	.120
• ½" GYPSUM WALL BOARD	.079(2)
• 6 MIL POLY VAPOUR BARRIER	0
• ½" PLYWOOD SHEATHING	.127(1)
• AIR BARRIER/SHEATHING MEMBRANE	0
• ¾" CAPILLARY BREAK GAP/AIR	.156
• 6 Mm (¼") FIBRE-CEMENT CLADDING	.020
• EXTERIOR AIR FILM	.030
	RSI(2.7)(R15.4)
CAVITY RSI (R-VALUE)	RSI = 1.7(1)
TOTAL EFFECTIVE INSULATION VALUE	RSI = 3.2(R)



BELOW GRADE WALL ASSEMBLY
1/4" = 1'-0"

ABOVE GRADE WALL ASSEMBLY WITH PLUMBING VENT/ELECTRICAL PANEL
(6 Mm FIBRE-CEMENT BOARD SIDING)

MINIMUM REQUIRED EFFECTIVE THERMAL RESISTANCE = RSI 1.78 (R 10.1)
2x6 STUDS @ 16" O.C.

ASSEMBLY DESCRIPTION	
• INTERIOR AIR FILM	
• ½" GYPSUM BOARD	
• 6 MIL POLY VAPOUR BARRIER	
• 2x6 STUDS @ 16" O.C.	
• 4" XPS INSULATION	
• ½" PLYWOOD SHEATHING	
• AIR BARRIER/SHEATHING MEMBRANE	
• ¾" CAPILLARY BREAK GAP/AIR	
• 6 Mm (¼") FIBRE-CEMENT CLADDING	
• EXTERIOR AIR FILM	
MATERIAL ELEMENTS	
• INTERIOR AIR FILM	.120
• ½" GYPSUM WALL BOARD	.079(2)
• 6 MIL POLY VAPOUR BARRIER	0
• ½" PLYWOOD SHEATHING	.127(1)
• AIR BARRIER/SHEATHING MEMBRANE	0
• ¾" CAPILLARY BREAK GAP/AIR	.156
• 6 Mm (¼") FIBRE-CEMENT CLADDING	.020
• EXTERIOR AIR FILM	.030
	RSI(2.7)(R15.4)
CAVITY RSI (R-VALUE)	RSI = 1.7(1)
TOTAL EFFECTIVE INSULATION VALUE	RSI = 3.2(R)

ABOVE GRADE WALL ASSEMBLY WITH PLUMBING VENT/ELECTRICAL PANEL
(HOLLOW BACKED VINYL SIDING)

MINIMUM REQUIRED EFFECTIVE THERMAL RESISTANCE = RSI 1.78 (R 10.1)
2x6 STUDS @ 16" O.C.

ASSEMBLY DESCRIPTION	
• INTERIOR AIR FILM	
• ½" GYPSUM WALL BOARD	
• 6 MIL POLY VAPOUR BARRIER	
• 2x6 STUDS @ 16" O.C.	
• 4" XPS INSULATION	
• ½" PLYWOOD SHEATHING	
• SHEATHING MEMBRANE	
• HOLLOW BACKED VINYL SIDING	
• EXTERIOR AIR FILM	
MATERIAL ELEMENTS	
• INTERIOR AIR FILM	.120
• ½" GYPSUM WALL BOARD	.079(2)
• 6 MIL POLY VAPOUR BARRIER	0
• ½" PLYWOOD SHEATHING	.127(1)
• AIR BARRIER/SHEATHING MEMBRANE	0
• HOLLOW BACKED VINYL SIDING	.120
• EXTERIOR AIR FILM	.030
	RSI(2.7)(R15.4)
CAVITY RSI (R-VALUE)	RSI = 1.7(1)
TOTAL EFFECTIVE INSULATION VALUE	RSI = 3.2(R)



EFFICIENCY PLUMBING VENT-ELECTRICAL PANEL WALL ASSEMBLY DETAIL
1" = 1'-0"

©COPYRIGHT EXACT DRAFTING INC. ALL RIGHTS RESERVED. THIS DRAWING AND ALL THEIR REMAINS THE EXCLUSIVE PROPERTY OF EXACT DRAFTING INC. AND CANNOT BE USED OR REPRODUCED WITHOUT EXACT DRAFTING INC'S WRITTEN CONSENT.

THIS DRAWING WAS PREPARED BY EXACT DRAFTING INC. THE MATERIAL IS IT REFLECTS THE BEST JUDGEMENT OF EXACT DRAFTING INC. IN LIGHT OF THE INFORMATION AVAILABLE TO IT AT THE TIME OF PREPARATION. ANY USE WITH A THIRD PARTY WHICH OF THIS DRAWING OR ANY RELIANCE ON OR DECISIONS TO BE MADE BASED ON IT ARE THE RESPONSIBILITY OF SUCH THIRD PARTIES. EXACT DRAFTING INC. ACCEPTS NO RESPONSIBILITY FOR DAMAGES, IF ANY, SUFFERED BY ANY THIRD PARTY AS A RESULT OF DECISIONS MADE OR ACTIONS TAKEN BASED ON THIS DRAWING.

Exact Drafting Inc.
Residential Building Design
Kelowna, BC V1Y 7T1
Phone: 250-763-4488
Fax: 250-763-4488
Email: exactdrafting@shaw.ca

Terrence Clark
4377 Prospect Road
West Kelowna
604-326-5395

4416 ALBERT STREET
PROPOSED HOUSE
DETAILS

SCALE: 1/4"=1'-0"
DATE: 07

A REDUCTION IN THE THERMAL RESISTANCE OF THE ATTIC INSULATION AT THE PERIMETER IS PERMITTED PROVIDED THE INSULATION IS CONSTRAINED ONLY BY THE ROOF PLANE AND VENTING REQUIREMENTS AND THE MINIMUM THERMAL RESISTANCE VALUE ABOVE THE EXTERIOR WALL IS AT LEAST R-19



ENERGY EFFICIENCY CEILINGS BELOW CATHEDRAL & FLAT ROOFS DETAIL
1/4" = 1'-0"



EFFICIENCY OF ATTIC CEILINGS BELOW ATTICS ASSEMBLY DETAIL
1/4" = 1'-0"

CEILINGS BELOW CATHEDRAL AND FLAT ROOFS

MINIMUM REQUIRED EFFECTIVE THERMAL RESISTANCE = R-19 (R-24 IF 2x10 JOISTS @ 24" O.C.)	
ASSEMBLY DESCRIPTION • EXTERIOR AIR FILM • 1/2" VENTED AIR SPACE • 5/8" TWO PLYER PLYWOOD SHEATHING • 2x10 JOISTS @ 24" O.C. • R-19 BATT FIBERGLASS INSULATION IN CAVITIES • 6 MIL FULLY VAPOR BARRIER • 5/8" GYPSUM BOARD • INTERIOR AIR FILM	
CONTINUOUS ELEMENTS • EXTERIOR AIR FILM • 1/2" VENTED AIR SPACE • 5/8" TWO PLYER PLYWOOD SHEATHING • 6 MIL FULLY VAPOR BARRIER • 5/8" GYPSUM BOARD • INTERIOR AIR FILM	.17 .70 .0994 0 .45 .68 R-19.4969
(UNIT) RSI (IP REALLY) $\frac{R}{U} = \frac{R_i}{U_i} + \frac{R_o}{U_o}$	R-19 = 4.96
TOTAL EFFECTIVE INSULATION VALUE	R-19 = 4.70

CEILINGS BELOW ATTICS - COMMON TRUSS

MINIMUM REQUIRED EFFECTIVE THERMAL RESISTANCE = R-19 (R-24 IF 2x10 COMMON TRUSS @ 24" O.C.)	
ASSEMBLY DESCRIPTION • EXTERIOR AIR FILM • 1/2" VENTED AIR SPACE • 5/8" TWO PLYER PLYWOOD SHEATHING • 2x10 COMMON TRUSSES @ 24" O.C. • CONTINUOUS LOOSE FILL FIBERGLASS INSULATION ON TOP OF CAVITIES • R-19 LOOSE FILL FIBERGLASS INSULATION IN CAVITIES • RAISED HEEL TRUSSES @ 24" O.C. IN: 5/8" BOTTOM CHORD • 6 MIL FULLY VAPOR BARRIER • 5/8" GYPSUM BOARD • INTERIOR AIR FILM	
CONTINUOUS ELEMENTS • EXTERIOR AIR FILM • ROOFING MATERIAL SHINGLES • 5/8" TWO PLYER PLYWOOD SHEATHING • R-19 FIBERGLASS LOOSE FILL INSULATION • 1/2" VENTED AIR SPACE • 6 MIL FULLY VAPOR BARRIER • 5/8" GYPSUM BOARD • INTERIOR AIR FILM	.17 .44 .0994 .70 .45 .68 R-19.4969
(UNIT) RSI (IP REALLY) $\frac{R}{U} = \frac{R_i}{U_i} + \frac{R_o}{U_o}$	R-19 = 3.84
TOTAL EFFECTIVE INSULATION VALUE	R-19 = 3.84

©COPYRIGHT EXACT DRAFTING INC. ALL RIGHTS RESERVED. THIS PLAN IS AND AT ALL TIMES REMAINS THE EXCLUSIVE PROPERTY OF EXACT DRAFTING INC. NO CHANGES OR USES MAY BE MADE WITHOUT EXACT DRAFTING INC'S WRITTEN CONSENT.

THIS DRAWING WAS PREPARED BY EXACT DRAFTING INC. THE MATERIAL IN IT REFLECTS THE BEST JUDGEMENT OF EXACT DRAFTING INC. IN LIGHT OF THE INFORMATION AVAILABLE TO US AT THE TIME OF PREPARATION AND USE WITH A THIRD PARTY MAKES OF THIS DRAWING OR ANY RELIANCE ON OR DECISIONS TO BE MADE BASED ON IT ARE THE RESPONSIBILITY OF SUCH THIRD PARTIES. EXACT DRAFTING INC. ACCEPTS NO RESPONSIBILITY FOR DAMAGES, IF ANY, SUFFERED BY ANY THIRD PARTY AS A RESULT OF DECISIONS MADE OR ACTIONS BASED ON THIS DRAWING.

Exact Drafting Inc.
#205-1111 West Hastings St. Vancouver, BC V6E 2J3
Phone: 604-688-2121 Fax: 604-688-2122

Terrance Clark
427 Prospect Road
North Vancouver 604-985-3985

448 ALBERT STREET
PROPOSED HOME
DETAILS

1/4"=1'-0"

A7
01

[illegible]

[illegible]

[illegible]	
[illegible]	
[illegible]	
[illegible]	

TOPOGRAPHIC PLAN OF LOT 3, BLOCK 5
DISTRICT LOT 121, GROUP 1
NEW WESTMINSTER DISTRICT
PLAN 1054

4412 - Albert Street
Burnaby, B.C.

ZONING: RM6

SCALE: 1 INCH = 16 FEET

0 5 10 20 30 50

All dimensions are in feet and decimals thereof unless otherwise indicated.
Contour interval: 1.0 feet

RECEIVED
NOV 12 2015
BUILDING DEPARTMENT

NOTE:
Elevations are based on Geodetic Datum.
Bench Mark: Control Monument DIS 310 located in the curb at the SW corner of Pender Street and Willingdon Avenue.
B.M. Elevation = 259.47 feet (79.085 metres)



NOTE:
All trees are plotted in accordance with Burnaby Tree Bylaw 1996 (No Trees)

© copyright restriction
This document is not valid unless originally signed and sealed.

CERTIFIED CORRECT:
November 5, 2015

B.C.L.S.

LEGEND:

● IP	iron post
■ LP	lead plug
◆ AP	aluminum post
TW	top of wall
SW	top of sidewalk
GU	gutter
CP	covered porch
LQ	living quarters
o/h	overhang
(G)	ground

All original corner posts have been located and are undisturbed, therefore a Posting Plan is not required.

NOTE:
The building envelope shown is only our interpretation of the City of Burnaby building bylaws. The size and location of the building envelope must be confirmed by the City of Burnaby planning department prior to any design work. Failure to confirm with the planning department will place the responsibility onto the house designer.

FRONT YARD SETBACK CALCULATIONS

HOUSE NO.	LOT NO.	MIN. FRONT SETBACK	AVERAGE
304	1	33.8	
4410	2	24.9	24.88
4416	4	19.8	MINIMUM
4420	LMS2334	21.0	19.69
	TOTAL	99.5	

NOTE:
For construction, use lead plugs in sidewalk or City survey monument only, for elevation control.

Ken K. Wong and Associates
Canada and B.C. Land Surveyors
5624 E. Hastings Street
Burnaby, B.C. V5B 1R4
Telephone: 294-8881
Fax: 294-0625
150757 K8906 P96-98
R-450 R-6243
SZ-5584
Drawn by: FB

FILE: TF-4885 PID: 002-848-970